

CANTER 2015

DELIVERING
lower cost-of-ownership.

FE130



MITSUBISHI FUSO TRUCK OF AMERICA, INC.



FE130

SPECIFICATIONS

A boost for your business and your bottom line. The Canter® will change the way you think about moving your company forward. Its cost-of-ownership is so low you can measure it by the mile—in dramatically improved fuel economy, service intervals, payload capacity and driver productivity. Its fuel-injected diesel engine and automated manual transmission set new benchmarks for efficiency and driving ease. They're backed by our industry-best 5-Year/175,000-Mile powertrain limited warranty. The Canter FE130. It's just the boost your business needs.



| | | | | | |
|---------------------------|--------------------------------|--|--------|--------|--------|
| Weight ratings | GVWR/GCWR | 13,200 lb./20,915 lb. | | | |
| | GAWR (front/rear) | 5,360 lb./9,880 lb. | | | |
| Curb weight | Base model | 5,225 lb. (est.) | | | |
| Body/Payload | Estimated max. | 7,975 lb. (see dealer for details) | | | |
| Dimensions | Wheelbase | 110.2 | 133.9" | 151.6" | 169.3" |
| | Overall length (cab/chassis) | 204.1" | 227.8" | 245.5" | 263.2" |
| | Usable cab to rear axle | 81.2" | 104.9" | 122.6" | 140.3" |
| | Body sizes accommodated | 10' to 20' | | | |
| Engine | Model | 4P10(T5) | | | |
| | Type | DOHC, 4-cylinder, 4-stroke cycle, water-cooled, turbocharged, intercooled diesel with 4 valves per cylinder | | | |
| | Displacement | 183 cu. in. (3.0 L) | | | |
| | Max. output (SAE, gross) | 161 hp @ 3,400 rpm | | | |
| | Max. torque (SAE, gross) | 295 lb.-ft. @ 1,300 rpm | | | |
| Air cleaner | Type | Dry paper element with snorkel | | | |
| Transmission | Standard equipment | Mitsubishi Fuso DUONIC® 6-speed OD AMT | | | |
| Axle capacity | Front | 5,735 lb. | | | |
| | Rear | 9,925 lb. | | | |
| Final reduction gear | Type | Single-reduction hypoid | | | |
| | Ratio (std/opt'l) | 4.875/5.285 | | | |
| Top speed, est. | Std diff/Opt'l diff | 90/83 mph | | | |
| Turning diameter | Minimum, by wheelbase | 34.1' | 40.0' | 44.6' | 49.5' |
| Tires (premium) | Configuration | Single front, dual rear | | | |
| | Size/Type | 215/85R16 10PR: LR:E/All-season all positions | | | |
| Wheels | Size/Configuration | 16" x 6"/5-lug | | | |
| Steering | Type | Ball-nut type with integral-type hydraulic power boost | | | |
| | Adjustments | Tilt/telescoping steering column with steering lock | | | |
| Suspension | Front | Laminated leaf springs with shock absorbers and stabilizer bar | | | |
| | Rear | Laminated leaf springs with shock absorbers | | | |
| Brakes | Service | Dual-caliper discs, vacuum/hydraulic-type with ABS | | | |
| | Parking | Drum/driveline, internal expanding shoe | | | |
| | Exhaust | Electrically actuated | | | |
| Frame | Type | Ladder/straight | | | |
| | Section modulus | 7.08 cu. in. per rail | | | |
| | Yield strength | 56,565 psi | | | |
| | RBM per rail | 400,410 lb.-in. | | | |
| | Height/Width | 32.5" / 33.5" | | | |
| Fuel tank | Capacity/Location—std.* | 30 gal./in-frame, aft of rear axle | | | |
| | Capacity/Location—opt.** | 33 gal./left side | | | |
| DEF tank | Capacity/Location | 3.2 gal./right side | | | |
| Battery | Type/Capacity | Two 12-volt, maintenance-free/750 CCA | | | |
| Electrical | Starter/Alternator | 12-volt/12-volt, 140A output | | | |
| Starting | Cold weather provision | Individual ceramic-tipped glow plugs | | | |
| Convenience/ Assurance | Windows/Door locks | Power-operated, one-touch up and down driver's-side window | | | |
| | Cruise control | Standard (programmable) | | | |
| | Entry | Keyless, with driver/assistant door lock control | | | |
| | Radio | Optional Clarion AM/FM/CD Bluetooth radio | | | |
| | Engine Protection System (EPS) | Automatic engine shutdown due to low oil pressure; automatic fuel reduction due to excessive coolant temperature | | | |
| | Idle Limit System (ILS)—opt. | Automatic engine shutdown of stationary vehicle after achieving normal operating temperature and specified limit of 3, 5 or 10 minutes | | | |

SAFETY

Crush bar in each door, energy-absorbing steering column, daytime running lights, dual-caliper disc brakes with ABS (all wheels), covered open-grate entry steps, forward-swing doors for safer entry/exit, high-visibility halogen headlamps, Engine Protection System (EPS)

CAB COLORS

ARCADIA SILVER

NATURAL WHITE

JUPITER GREEN

MARS RED

SHANNON BLUE

SOLID BLACK

All models are available immediately in white. Other colors shown (except Solid Black) may be special-ordered at no extra charge. Accuracy of indicated hues is limited by paper/electronic reproduction.

FABRIC STYLE

BLUE CLOTH

Vehicle specifications are subject to change without notice. Photos and descriptions included in this spec sheet may vary in comparison to actual vehicle models. For warranty limitations and details, see your local dealer.

PRINTED IN THE U.S.A. 5/14.
©2014 MITSUBISHI FUSO TRUCK OF AMERICA, Inc.

Mitsubishi Fuso Truck of America, Inc.

2015 Center Square Road
Logan Township, NJ 08085

mitfuso.com

*rear fuel tank is not designed for use as a primary or auxiliary in any dual tank system
**133.9", 151.6", 169.3" wb

